

# VANCOUVER 90 ROUND 5752

SKU 1229012

astro



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                   |                        |  |
|----------------------------------|-------------------|------------------------|--|
| <b>FINISH:</b>                   | Clear Acrylic     | <b>CABLE LENGTH:</b>   | 450 (mm)                                     |
| <b>MAIN MATERIAL:</b>            | Plastic - Acrylic | <b>GROSS WEIGHT:</b>   | 0.37 (Kg)                                    |
| <b>DIMENSIONS:</b>               | D:66mm DIA: 90mm  | <b>CLASS:</b>          | CE (Class III)                               |
| <b>INSTALLATION ORIENTATION:</b> | Ceiling Mount     | <b>IP RATING:</b>      | IP44   |
| <b>CUT OUT HOLE:</b>             | 76mm/3"           | <b>BATHROOM ZONE:</b>  | Zone 2, 3                                    |
| <b>RECESS DEPTH:</b>             | 86 (mm)           | <b>VOLTAGE:</b>        | Constant Current 350 (mA)                    |
| <b>FIRE RATING:</b>              | Not Applicable    | <b>PRODUCT F MARK:</b> | Suitable for mounting on flammable materials |

### LAMP

|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | COB LED        | <b>MACADAM ELLIPSE:</b>           | 3-Step         |
| <b>MAXIMUM WATTAGE:</b>     | 6W             | <b>UGR:</b>                       | To Be Advised  |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | Not Applicable |
| <b>LAMP INCLUDED?</b>       | Yes (Integral) | <b>TILT ADJUSTMENT ANGLE:</b>     | Not Applicable |
| <b>LUMINOUS FLUX:</b>       | 680.9 (lm)     | <b>ROTATION ADJUSTMENT ANGLE:</b> | Not Applicable |
| <b>COLOUR TEMP:</b>         | 3000 (K)       | <b>AVERAGE LIFESPAN:</b>          | 36,300 (Hrs)   |
| <b>CRI:</b>                 | 80             | <b>L70:</b>                       | To Be Advised  |
| <b>R9:</b>                  | 12.0           |                                   |                |

### ELECTRICAL

|                               |                        |                                 |                |
|-------------------------------|------------------------|---------------------------------|----------------|
| <b>SWITCHED:</b>              | No                     | <b>SUPPLY FREQUENCY:</b>        | Not Applicable |
| <b>DIMMABLE:</b>              | Yes                    | <b>DRIVER/BALLAST VOLTAGE:</b>  | Not Applicable |
| <b>DIMMING METHOD:</b>        | Control Gear Dependant | <b>DRIVER AVERAGE LIFESPAN:</b> | Not Applicable |
| <b>DRIVER OUTPUT CURRENT:</b> | Not Applicable         | <b>EFFICACY:</b>                | 111.62 (lm/W)  |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable         | <b>DRIVER/BALLAST INCLUDED?</b> | Not applicable |

## ADDITIONAL INFORMATION

CE



BOX QUANTITY x 20

## PRODUCT ELEVATIONS

**GB** Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

**FR** Veuillez noter que certaines dimensions peuvent varier légèrement en raison des tolérances de fabrication, y compris l'entrée de câble et les trous de fixation.

**DE** Bitte beachten Sie, dass die Maße Fertigungstoleranzen unterliegen und daher in geringem Umfang von der angegebenen Größe abweichen können. Dies gilt auch für Kabeleingänge und Befestigungslöcher.

**IT** Si prega notare che possono esserci piccole variazioni in alcune dimensioni dovute alle tolleranze di produzione, queste includono l'ingresso del cavo e i fori di fissaggio.

